

LUKOIL BRAKE FLUID DOT 4

High performance premium brake fluid

Approvals

- DOT 4
- SAE J1704
- FMVSS No. 116

Product description

High Performance Brake Fluid manufactured from poly- glycol, borate esters and other inhibitor additives for use in drum and disc type braking systems of auto motive vehicles working under severe conditions. The low volatility & low pour point ensures performance in normal temperature ranges. Provides excellent protection against rust and corrosion. It is compatible with rubber seals. Good braking response. Reduces chance of vapor lock.

Application

Recommended where DOT 4 brake fluids are preferred and is not recommended where DOT 5 brake fluids are specified. Designed for use in all light and heavy-duty vehicles.

Benefits

MAXIMUM PROTECTION

Maximum protection - Long service life due to excellent oxidation stability

UNIVERSAL APPLICATION

Carefully selected formulation – widely compatible with other brake fluids

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D4052	1.035
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	2.10
Kinematic viscosity at -40 °C, mm ² /s	ASTM D445	1130
Dry Boiling Point, °C	ASTM D1120	260
Wet Boiling Point, °C	ASTM D1120	165
pH	ASTM D1287	8.5