

LUKOIL GENESIS UNIVERSAL GASOLINE 10W-40

Synthetic Technology Engine Oil

Meets Requirements & Specifications

- API SN
- ACEA A3/B3, A3/B4
- PSA B71 2294/2300
- Renault RN 0700/0710
- Fiat 9.55535-G2
- MB 229.3
- API CF

Product description

Multigrade engine oil based on synthetic technology for modern after-warranty passenger cars. Designed with Synthactive® innovative technology provides increased engine efficiency and fuel-economy. Compatible with exhaust catalytic converter system (TWC).

Application

Recommended for all-season use in gasoline both non-charged and turbo-charged and diesel engines (without DPF) of modern cars and light trucks, which require API SN and/or ACEA A3/B3, A3/B4 performance level and SAE 10W-40 viscosity.

Benefits

MAXIMUM PROTECTION

Provides excellent protection against wear in severe operating conditions

EASY COLD START

Synthetic base oil provides easy cold start-up

OXIDATION RESISTANCE

Excellent resistance to oxidation and nitration due to the high Total Base Number

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D4052	863
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	14,90
Viscosity index	ASTM D2270	159
Apparent viscosity (CCS) at -25 °C, mPa s	ASTM D5293	5,800
Borderline pumping viscosity (MRV) at -30 °C, mPa s	ASTM D4684	25,720
Total base number, mg KOH/g	ASTM D2896	8,3
Flash Point, COC, °C	ASTM D92	232
Pour Point, °C	ASTM D97	-39
Sulphated ash content, %	ASTM D874	1,05
Noack evaporation loss, %	ASTM D5800	10,3