

LUKOIL LUXE 15W-40

High quality multigrade mineral engine oil

Meets Requirements & Specifications

- API SL/CF
- PJSC "ZMZ"
- PJSC "AVTOVAZ"

Product description

A high-quality mineral multigrade oil for use in petrol engines. Provides high anti-wear, anti-oxidation and anti-corrosion properties.

Application

Intended for use in gasoline and diesel engines of passenger cars, vans and light trucks, where API SL/CF performance level is required. Blended on high- quality mineral base stocks and robust additive package.

Benefits

REDUCED NITRATION & OXIDATION

Excellent antioxidant and anti-corrosion properties

ASH DEPOSIT CONTROL & CLEANLINESS

Reduced ash deposits and Improved detergent and dispersant properties

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D4052	881,9
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	14,5
Viscosity index	ASTM D2270	137
Apparent viscosity (CCS) at -20 °C, mPa s	ASTM D5293	5,360
Borderline pumping viscosity (MRV) at -25 °C, mPa s	ASTM D4684	30,070
Total base number, mg KOH/g	ASTM D2896	6,4
Flash Point, COC, °C	ASTM D92	234
Pour Point, °C	ASTM D97	-36
Sulphated ash content, %	ASTM D874	0.96
Noack evaporation loss, %	ASTM D5800	10,1