

LUKOIL MOTO 4T 10W-30

Synthetic Technology 4-Stroke multigrade motorcycle engine oils

Meets Requirements & Specifications

- API SL
- JASO MA2

Product description

Modern 4-Stroke engine oil for motor-cycles, mopeds and scooters based on synthetic technology. The oils provide highly-effective protection for the engine, perfect transmission operation and optimum clutch performance, has excellent detergent and antioxidant performance, improved anti-wear, anti-corrosion and antifoam properties.

Application

Recommended for all-season use in 4 stroke engines, transmissions and clutches of modern motorcycles when they require lubrication by motor oil. Exceed the requirements of all Japanese and American motorcycles manufacturers and are recommended where API SL and SAE 10W-30 grade are required.

Benefits

REDUCED OIL CONSUMPTION

Reduced oil consumption, wear and noise level during operation under high loads and temperatures

EASY START

Excellent low temperature properties for easy starting at low temperatures

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D4052	878,1
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	10,90
Viscosity index	ASTM D2270	138
Apparent viscosity (CCS) at -25 °C, mPa s	ASTM D5293	5,800
Borderline pumping viscosity (MRV) at -30 °C, mPa s	ASTM D4684	20,070
Total base number, mg KOH/g	ASTM D2896	9,35
Flash Point, COC, °C	ASTM D92	224
Pour Point, °C	ASTM D97	-39
Sulphated ash content, %	ASTM D874	1,08
Noack evaporation loss, %	ASTM D5800	12,0