

LUKOIL BRAKE FLUID DOT 3

Meets requirements

- DOT 3
- SAE J1703
- FMVSS No. 116

Product description

High-performance polyglycol based fluid suitable for use in disc and drum brakes and hydraulic clutch systems where a non-petroleum based DOT 3 fluid is specified.

Application

Recommended where DOT 3 brake fluids are preferred and is not recommended where DOT 4, Super DOT 4 or DOT 5 brake fluids are specified.

Designed for use in all light and heavy-duty vehicles.

Benefits

MAXIMUM PROTECTION

Maximum protection - Long service life due to excellent oxidation stability

UNIVERSAL APPLICATION

Carefully selected formulation – widely compatible with other brake fluids

Typical test data

The information given in the typical data does not constitute a specification and can be affected by allowable production tolerances. The right to make modifications is reserved by OOO «LLK-International»

Property	Test methods	Value
Density at 15 °C, kg/m ³	ASTM D4052	1.065
Kinematic viscosity at 100 °C, mm ² /s	ASTM D445	2.05
Kinematic viscosity at -40 °C, mm ² /s	ASTM D445	1250
Dry Boiling Point, °C	ASTM D1120	240
Wet Boiling Point, °C	ASTM D1120	160
pH	ASTM D1287	8.9